



The JIVA 5000 touch terminal series by POSIFLEX offers features such as a software controlled on/off switch to prevent accidental shutdown, optional internal UPS (uninterruptible power supply), and an integrated finger print/MSR (magnetic stripe reader) attachment. With a unique space saving stand design, all JIVA 5000 include a wall mount bracket, rear mount bracket for optional 2nd display, primary hard drive, and optional built-in battery. The base design is intended to provide POSIFLEX business partners added flexibility when installing the JIVA terminal. The JIVA 5000 series services hospitality, retail, gaming, kiosk, healthcare, c-store, petroleum, grocery and a variety of vertical markets.

5000 Series



All Blue Ridge terminal models can bundle with

- SD200 series 2-in-1 attachment MSR and/or U.are.U finger print sensor
- CR4000 series Cash Drawer
- PP7000 series Aura Thermal Receipt Printer
- PD2000 series Pole Display or PD302 customer display
- KB6000 series Programmable keyboard

Specifications

Model	JIVA 5715 (Thin-Client)	JIVA 5815
Max. LCD Resolution:	1024 x 768	
Brightness:	250 nit/m ²	
LCD Panel:	15.1" dual backlit LCD panel TFT active matrix	
Touch Sensor:	Accutouch, resistive type	
CPU:	C3 800GHz	C3 1.0 GHz
Memory:	256MB, DDR 266, SDRAM x 2 DIMM up to 1 GB	
Video Memory:	16MB (expandable to 64MB)	
Audio Line Output:	Standard (Audio Amp + Speakers option)	
Serial Port:	4 available with PS/2 touch interface	With +5VDC 4 available with PS/2 touch interface, 3 available with RS232 touch controller interface
Parallel port:	1	
CR Port:	1 port controls 2 devices (under COM1)	
USB Port:	2	
KB Port:	1 x PS/2 type	
Mouse Port:	1 x PS/2 type	
Lan Port:	10/100 MHz base Ethernet	
HDD:	N/A	Built-in 3.5", 20GB
FDD:	3.5" external USB interface (option)	
OS Support:	WinCE	Windows XP Professional / WEPOS
Compact Flash Port:	1 Type II connector (compact flash memory card is option)	N/A
Internal UPS	Yes (Battery Optional)	
ON/OFF Control:	Software controlled for Mechanical ON/OFF or Mechanical ON Software OFF	
Tilt Adjustment:	From 17.5° to 87.5°	
Mounting Option:	Table top or Wall mounted	
Housing Color:	Charcoal	
Power Supply:	AC adaptor: input 100-240V, output DC 12V/80W	
Dimension:	14.8" (W)x11.1" (D) x11.7"-14.7" (H)	
Safety Certifications:	PSU: UL / VDE / T mark Terminal: FCC, CE (meet IEC 100-4-2 class A)	

All Blue Ridge terminal models come standard with integrated wall-mount bracket, rear mount bracket for optional 2nd display, primary hard drive and optional built-in battery.

JIVA 5000 series with Slim Type 4-in-1 Base Stand



Available Peripherals

