



- NOTES: 1. ACCESSIBLE PARKING AS CLOSE TO BUILDING ENTRANCE AS POSSIBLE.  
 2. DESIGNATED RESERVED SIGN BY EACH SPACE  
 3. EACH PARKING LOT SHALL HAVE A MINIMUM OF ONE (1) "VAN ACCESSIBLE" SPACE.  
 4. ONE IN EVERY EIGHT (8) ACCESSIBLE SPACES SHALL HAVE AN ACCESS AISLE 8'-0" WIDE AND SHALL BE SIGNED- "VAN ACCESSIBLE".

5. SIGNS SHOULD HAVE THE INTERNATIONAL "ACCESSIBLE SYMBOL" W/"VAN ACCESSIBLE" INDICATED BELOW.  
 6. RAMP MAXIMUM SLOPE 1:12.  
 7. OTHER AS REQUIRED BY ADA STANDARDS.

ACCESSIBLE PARKING SPACES (REQUIRED MINIMUM)	
TOTAL PARKING SPACES IN LOT	ACCESSIBLE SPACES
1 TO 25	1
26 TO 50	2
51 TO 75	3
76 TO 100	4
101 TO 150	5
151 TO 200	6
201 TO 300	7
301 TO 400	8
401 TO 500	9
501 TO 1,000	2*
1,001 AND OVER	20**

\* PERCENT OF TOTAL  
 \*\* PLUS ONE SPACE FOR EACH 100 OVER 1,000