

You will need the "Fit to Be Square Ruler" by Open Gate Quilts And Eleanor Burns, Quilt In A Day 11/2"x3" Finished Flying Geese Ruler

> Formatted byThea Jirak of Quilting Delights for 2012 Block of the Month Program. All rights to this pattern belong to Open Gate Quilts except as transferred to Quilting Delights. This pattern is copyrighted and **permission is not granted to make copies**. Copies are available through Quilting Delights, www.quiltingdelights.com, (503) 658-1600, 14863 SE Oregon Trail Drive, Clackamas, OR 97015. Thank you.

Step 1 and 2 - Quarter Square Triangles and Half Square Triangles - Make 4 of each

Step 1 - Sew the Blue Floral and Background
4½" squares together as shown. Right sides
together and 1/4" on either side of the center
line. Cut apart and press. DON'T SQUARE UP!

Rotate half of your HST's and place the squares right sides together with the seams nesting. Again, mark your center line perpendicular to the seam and sew 1/4" on either side. Cut



apart between the seams and press open. NOW square up to $3\frac{1}{2}$ "

Step 2 - Sew the Black and Background 2¹/₂" squares together as shown. Right sides together and 1/4" on either side of the center line. Cut apart and Lightly Press. Square to 2".



Step 3 - Flying Geese - Make 4 and 8

Using the Eleanor Burns method of assembly, Take the 6" Square of Red and the 41/2" square of Background and make 4 Flying Geese.


Take the two 6" Squares of Black and the two $4\frac{1}{2}$ " squares of Blue Floral and make 8 Flying Geese.

Square up to $2''x3\frac{1}{2}''$. To do this, separated the "raw" Flying Geese. Use your ruler and cut the top 1/4'' seam allowance across the tip of the triangle FIRST! Turn and cut the bottom of the triangle at 2'' Then cut the sides

Make 4



Make 8



Assemble in rows as shown to the right with the blocks from Step 1 through 3, the Center $3\frac{1}{2}$ " square and the corner $3\frac{1}{2}$ " squares.

Pressing is really the path of least resistance on this block. The way I did mine was to make the rows and then turn it over and see which way they landed. Then checked the second and third rows and on and on.

The real trick here is to carefully match the seams when you put the rows together. A simple way to do this is to use the "pin" technique. You place a pin through the top and bottom rows where you want the seams to match. Hold that pin straight up and down and pin the fabrics together. Carefully sew and check your work!

