

SERGERS







Create Precise Seam Finishes

3/4 thread (1 or 2 needles)

• Create a precise seam finish for professional garment appearance with household sewing needles.

Color-coded thread guides and tension disks

 Allows for easy upper and lower looper threading and quick thread changes with all thread types.

Stitch length 0.8mm to 4.0mm

• Suitable for any type of project and easily adjustable with stitch width dial.

Differential feed ratio of 0.7 to 2.0

 Improves stitch quality on all types of fabric and acts as the tool for custom lettuce edge finishes on specialty fabrics.

Free-arm serging

 Removable table section makes serging cylindrical pieces quick and easy.

Stitch width 3.0mm to 7.0mm

 Adjustable to provide the perfect stitch width, especially on lightweight fabrics or to create the popular rolled hem on napkins and tablecloths.

Up to 1,300 stitches per minute

• Saves time when sewing and completing serged edges.

Dual use removable trim trap

• Collects fabric as the adjustable serger knife trims and serges.

Specialty feet included

• Blind stitch foot and gathering foot.

Included bilingual operation manual and 12-section informational DVD

Overview

Give a professional look to your next project with serged seam finishes. Seams lie flatter and look better with an overlock stitch. Home décor projects often suggest the use of a serger for rolled hems, secure seams and differential feed. Choose from a 3 or 4 thread look and enjoy the new and easy threading method. The 3034D features two needles and 3/4 thread with differential feed. Create stitches from 0.8 to 4.0 mm

in length. The differential feed ratio of 0.7 to 2.0 gives improved stitch quality and the free arm makes it easier to sew sleeves, trouser legs and other hard to reach places.

Basic Features

Dusic realores	
Threads	3/4
Number of Needles	2
Overlock Seam Width	3.0 - 7.0
Double Chain Stitch	_
Cover Stitch	_
Stitch Length (mm)	0.8 - 4.0
Stitch Width (mm)	3.0 - 7.0
Differential Feed	0.7 - 2.0
Change for Rolled Hemming	Removable
Needle Threading System	-
Underlooper Threader	•
2/3 Thread Change	-
Color-Coded Thread System	•
Adjustment for Thread Tightness	-
Stitch Fingers	1
Knife Drive Type	Down Side
Thread Tension System	Manual
Electronic Speed Control	-
Presser Foot Pressure Adjustment	•
On Screen Prompts	-
Free Arm	•
Light	Normal Light
Wide Table	-
Specialty Feet Included	•
Maximum Sewing Speed (stitches per minute)	1,300

3034D

For more information, visit www.brother-usa.com or call 1-800-4-A-BROTHER

