

# **SERGERS**







# Cover Stitch

#### Wide variety of cover stitches, from utility to decorative

Professionally finish edges with single or dual top-stitching look.
Finish interior edges and attach decorative edging at the same time.
Create durable strapping for swimsuits and dance garments, chain stitch finish for hems or belt loops.

#### Color-coded upper thread dials and looper thread guides

• Allows for easy threading.

#### 1-2-3 needle options

 Utility, flatlock and decorative stitches have even more possibilities with a variety of needle positions.

#### Stitch length 2.0mm to 4.0mm

• Suitable for many types of projects.

#### Fast-easy looper threading system

 Color coded with thread management guides to assure proper thread delivery.

#### Slide lever adjustment for differential feed

 A professional edge finish reduces the wavy or stretch appearance of stitches on fabrics.

#### Fully extendable thread guide

 Numerically coded guides for specialty threads; spool guides and thread nets for serger thread and domestic thread spools.

#### Presser foot pressure dial

• Adjustable dial assures consistent fabric delivery.

#### Included operation manual

### Overview

The 2340CV Cover Stitch is an advanced serger, which allows you to create a wide range of cover stitches on all types and weights of fabric for both decorative and constructive applications. Expand your creativity with the 2340CV's advanced

technology. It features a tri-cover stitch, wide and narrow cover stitches, color-coded threading, easy looper threading, adjustment dials for stitch length, a presser foot dial, snap on feet and differential feed which allows you to alter the speed at which

your fabric is feeding through the machine. With 3 needles and one looper thread, the cover stitch machine creates professional hems, chain stitch and decorative stitching great for making the perfect T-shirt in no time!

### **Basic Features**

Threads	2/3/4
Number of Needles	3
Overlock Seam Width	-
Double Chain Stitch	•
Cover Stitch	•
Stitch Length (mm)	2.0 - 4.0
Stitch Width (mm)	3.0 or 6.0
Differential Feed	0.7 - 2.0
Change for Rolled Hemming	_
Needle Threading System	_
Underlooper Threader	-
2/3 Thread Change	
Color-Coded Thread System	•
Adjustment for Thread Tightness	-
Stitch Fingers	-
Knife Drive Type	-
Thread Tension System	Manual
Electronic Speed Control	-
Presser Foot Pressure Adjustment	•
On Screen Prompts	-
Free Arm	-
Light	Normal Light
Wide Table	-
Specialty Feet Included	•
Maximum Sewing Speed (stitches per minute)	1100

2340CV

For more information, visit www.brother-usa.com or call 1-800-4-A-BROTHER

