

ADDING BORDERS ON A QUILT

Measurements should be taken across the center of the quilt in two or three places for both the width and length.

1. Determine the length of the quilt border by averaging the two or three center measurements of the quilt body.
2. Cut two borders that length and pin them to opposite sides of the quilt. Match the ends and centers, then gently ease in any fullness.
3. Pin, sew, and press.
4. Repeat for the top and bottom borders measuring the width, averaging etc.

This is one of the most common problems. Borders that do not fit the quilt..... Ask for more information.

Quilt N Bee

506 C Ave
Cache, OK 73527
580-429-2400
www.quiltndbee.biz
info@quiltndbee.biz

Quilt N Bee

CUSTOM MACHINE QUILTING FOR
THE BUSY QUILTER
TURNING PIECED TOPS INTO HEIRLOOMS

(580) 429-2400
www.quiltndbee.biz



Quilt N Bee

506 C Ave
Cache, OK 73527
580-429-2400
www.quiltndbee.biz
info@quiltndbee.biz

Quilting Charges

Basting \$0.005/sq. inch
(This service is for those who want to hand quilt)

Edge to Edge (6" & up) \$0.020/sq. inch
(2 cent)

Binding Prep \$10

Binding added to front of quilt \$0.12/linear inch

Binding completely finished \$0.24/linear inch

Backing Prep \$10

EXAMPLES OF APPROXIMATE PRICES FOR STANDARD SIZES (PRICES ROUNDED)

size	sq inches	baste	edge to edge	
TWIN	68x90=6120	\$31	\$122	
DOUBLE	80x90=7200	\$36	\$144	
QUEEN	90X96=8640	\$43	\$173	
KING	96X108=10368	\$51	\$210	
XXL KING	120X120=14400	\$72	\$288	

Wide Backings

Wide Backs (108 x 108)

Wide backings are available for your project. Please see web site for current selection.

Batting

Hobbs 80/20 96" wide \$10.08/yd

Hobbs poly down 96" wide \$9.00/yd

Washable Wool \$19.36/yd

The batting come 97" wide, we sell it by the inch.

Threads

There will be a standard thread charge \$6.

Rush Orders

I will be happy to accommodate rush orders. There will be an extra charge of 75.00.

****Prices subject to change****

Preparing Your Quilt for Quilting

The quilt backing and batting should be a total of 8" bigger than the quilt top. This allows 4" on all sides for the squaring and loading onto the rollers of the quilting machine. Please press your quilt top and check all your seams to make sure none are loose. If you have pieced borders such as squares set together, run a stay stitch around the quilt. This will keep any seams from popping open when it is stretched across the machine rollers.

If your quilt has a definite top please indicate it with a piece of paper pinned to the correct side. If you have a border set preference please indicate that also. For example if you would like your borders to lay all up when the quilt is draped on the bed then preparation needs to be made.

Check all loose threads as the foot of the machine could catch on them and tear or pull a seam.

Clean finish and square up your backing. I will do this for you but I will charge for the service. Loose thread interferes with the wheels on the quilting machine.

Please remember that I want to do the best possible quilting job for you. If you have concerns or questions, please discuss them.