

BBW Long arm series

High speed, Single needle, Long (26 inch) arm, Compound feed and walking foot, Lockstitch sewing machine with automatic thread trimmer, Automatic backtack, Automatic presser foot lift, Climbing device and dual stitching device



BBW-8BLC-26-BTFL-CD-DS

Variety



BBW-8BLC-26

Compound feed and walking foot, reverse stitch, thread trimmer



BBW-8BLC-26-BTFL-CD-DS

Compound feed and walking foot, reverse stitch, thread trimmer, automatic back tack, automatic presser foot lift, climbing device, dual stitching device

Applications

For sewing medium to heavy weight materials such as leather, vinyl, synthetics and laminated and coated materials

Suitable for sewing such as automobile upholstery, tarpaulins, covers, awnings, tents, umbrellas handbags, luggage, travelware accessories, sports and camping equipment and wearing apparel outdoor clothing.



BBW Long arm series

Features (BBW-)

26 inch long arm, Longer stitch length quiet sewing operation. Max. 9mm for both forward and reverse feed stitching.

BBW series are equipped with a large vertical axis hook (1.6 times).

Safety device & Reliable thread trimming device & One touch switchover for two different stitch lengths (DS device).

Built-in bobbin winder & Wide working space (660mm).

Large clearance under presser foot. Presser bar lifter.

Simple setting for alternating presser foot movement. Smooth stitching on step section (CD device).

5 operational switches improve working efficiency.



Specifications (BBW-)

Variety	BBW-8BLC-26	BBW-8BLC-26-BTFL-CD-DS
Number of needle	Single needle	
Max. sewing speed	3,000 s.p.m.	
Max. stitch length	9mm (Forward / Reverse)	
Clearance under presser foot	9mm (by hand) 16mm (by knee)	9mm (by hand) 16mm (by automatic foot lifter)
Needle bar stroke	34mm	
Needle	135x17 Nm110 ~ Nm200 (Nm160) or DPx17 # 18 ~ # 25 (# 23)	
Thread	# 30 ~ # 5 (Standard # 8)	
Hook	Large vertical axis hook (1.6 times)	
Thread length after trimming	27mm	
Thread take up lever	Link type	
Amount of walking foot movement	1~7mm	
Walking foot movement change switch	Dial type	
Bobbin winder	Built-in type located at the top of the sewing machine	
Auto presser foot lifting device	Pneumatic	
Walking foot movement change device	Pneumatic	
Safety device	Standard	
Lubrication	Automatic lubrication type	
Bed size / Working space	925mm(W)x177mm(D) / 660mm(W)x120mm(H)	
Net weight (Head only)	74Kg	75Kg
Motor	AC Servo motor	

NOTE (1) Speed depends on threads, materials and type of operation

(2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan

Phone : +81-47-420-3561 (Overseas dept.)

Fax : +81-47-420-3560

E-mail : export@seiko-sewing.co.jp

<http://www.seiko-sewing.co.jp/>