


CW series


Single needle, High speed, Cylinder bed, Vertical axis hook, Lockstitch machines





CW-8B-2

Variety

- 

CW-1
No Feed
- 

CW-7B
Compound feed, reverse stitch
- 

CW-8B-2
Compound feed and walking foot, reverse stitch
- 

CW-8BV
Compound feed and walking foot, reverse stitch, synchronized binder



CW-1



CW-8BV

Applications

For darning and mending all types of medium to heavy weight materials. (CW-1)

Designed for stitching tubular and curved work.

Suitable for sewing such products as caps, cushions, boots, shoes, bags, luggage, handbags, travelware accessories, etc. (except CW-1)



Features

Vertical axis hook.

Safety clutch prevents the hook from being damaged.

No Feeding mechanism allows sewing work in any direction as required for darning and mending.
(-1 only)

Reverse stitching (except -1).

Compound feed and walking foot mechanism assures even feeding of materials.
(-8B-2, -8BV)

No Reverse stitch version available.

Semi-automatic lubrication system and large hook machines are available. (LCW series)

Specifications (CW-)

Variety	1	7B	8B-2	8BV
Number of needle	Single needle			
Max. speed	2,800(s.p.m.)	2,500(s.p.m.)		
Max.stitch length	13/64" (5 mm)			11/64" (4.5 mm)
Clearance under presser foot	by pedal	25/64" (10 mm)	25/64" (10 mm)	35/64" (14 mm)
	by hand		21/64" (8.5 mm)	21/64" (8.5 mm)
Needle bar stroke	1-5/16" (33.2 mm)			
Needle(standard)	FOx3 (#18) FOx3 (#110)	DPx17 (#22) , 135x17 (#140)		DPx17 (#18) 135x17 (#110)
Thread	#8 (standard)			
Hook	Vertical axis hook			
Amount of lift of walking foot				7/64"-7/32" standard 1/8" (2.7 - 5.5 mm) (standard 3.2 mm)
Thread take up lever	Slide type			
Lubrication	Hand type			
Cylinder size	2-9/16"(65 mm) dia.			
Working space	10-5/32"x 4-21/64" (258 x 110 mm)			
Motor	Clutch motor			
Net weight(Head only)	32Kg			

NOTE

- (1) Speed depends on threads, materials and type of operation
- (2) Specifications subject to change without notice

Optional parts and attachments at extra charge

Variety	Parts name & No.				
	Finger guard	Belt cover	Binder	Feed dog ("L"shape)	Vibrating p.f. ("L"shape)
1		13425C			
7B	10955-01	13425C			
8B-2	10937	13425C			
8BV	10937	13425C	2A type (2-fold) 3A type (3-fold)	13244	13250



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan
Phone : +81-47-420-3561 (Overseas dept.)
Fax : +81-47-420-3560
E-mail : export@seiko-sewing.co.jp

<http://www.seiko-sewing.co.jp/>