

JW single & two needle series

Single & Two needle, Extra heavy duty, Extra long arm, Extra large vertical axis hook, Compound feed and walking foot, Lockstitch machines




JW-28BL-10
10 inch machine arm


Variety


JW-8BL-10
10 inch machine arm, reverse stitch

JW-28BL-10
10 inch machine arm, reverse stitch

Auto thread trimmer

 JW-8BLC-20
20 inch machine arm, reverse stitch

 JW-28BLC-20
20 inch machine arm, reverse stitch

 JW-8BLC-30
30 inch machine arm, reverse stitch

 JW-28BLC-30
30 inch machine arm, reverse stitch



Clutch driven puller feed

Applications

For sewing extra heavy weight materials such as canvas, vinyl, leather, synthetics, and various coated, laminated and rubberized fabric.


Suitable for sewing such as tents, tarps, awnings, truck covers, auto marine and furniture upholstery, field covers, fabric structures and heavy bulky products.



JW single & two needle series

Features

- Long and wide working space is suitable for sizable materials such as tents and sail clothes.
- Extra large vertical axis hook.
- Compound feed and walking foot mechanism assures even feeding of materials.
- Automatic hook lubrication.
- Safety clutch prevents the hook from being damaged.
- Reverse feed operated by foot pedal.
- Push button stitch regulator.
- Built-in bobbin winder. (except 10 inch model)
- Front handwheel (30 inch model only) allows for easy positioning of the needle.
- Cloth puller available. Add suffix "R" when ordering.
- Automatic back tack(BT) and foot lift(FL) available.



Extra large vertical axis hook

Specifications (JW-)

Variety	8BL-10	8BLC-20	8BLC-30	28BL-10	28BLC-20	28BLC-30
Number of needle	Single needle			Two needle		
Max. sewing speed	1,500 s.p.m.	1,200 s.p.m.		1,500 s.p.m.	1,200 s.p.m.	
Max. stitch length	25/64" (10 mm)					
Clearance under presser foot	by pedal					
	by hand					
Needle bar stroke	1-27/32" (46.8 mm)					
Needle(standard)	DYx3 (#24) , 794 (#180)					
Thread	#5 (standard)					
Hook	Extra large vertical axis hook					
Amount of lift of walking foot	15/64" - 11/32" standard 15/64" (6 mm - 9 mm) (standard 6 mm)					
Thread take up lever	Slide type					
Lubrication	Semi-automatic type					
Bed size	20-25/64"x 7" (518 x 177 mm)	33-5/16"x 9-1/16" (846 x 230 mm)	43-5/16"x 9-1/16" (1,100 x 230 mm)	20-25/64"x 7" (518 x 177 mm)	33-5/16"x 9-1/16" (846 x 230 mm)	43-5/16"x 9-1/16" (1,100 x 230 mm)
Working space	10"x 6-1/32" (254 x 153 mm)	20"x 6-1/32" (508 x 153 mm)	30"x 6-1/32" (762 x 153 mm)	10"x 6-1/32" (254 x 153 mm)	20"x 6-1/32" (508 x 153 mm)	30"x 6-1/32" (762 x 153 mm)
Motor	Clutch motor or AC Servo motor					

NOTE (1) Speed depends on threads, materials and type of operation
(2) Specifications subject to change without notice

Available needle gauge size

Variety	Available needle gauge size range
28BL-10	3/16"(4.8 mm) - 1-3/4"(44.5 mm) standard 3/4"(19.1 mm)
28BLC-20	3/16"(4.8 mm) - 2"(50.8 mm) standard 3/4"(19.1 mm)
28BLC-30	3/16"(4.8 mm) - 2"(50.8 mm) standard 3/4"(19.1 mm)



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan

Phone : +81-47-420-3561 (Overseas dept.)

Fax : +81-47-420-3560

E-mail : export@seiko-sewing.co.jp

<http://www.seiko-sewing.co.jp/>