

LSW single needle series (plain)

High speed, Large vertical axis hook, Compound feed and walking foot, Reverse stitch, Lockstitch machines



LSW-8BL

Variety



LSW-8BL

Compound feed and walking foot, reverse stitch, large vertical hook.

Applications

For sewing medium to heavy weight fabrics, leather, vinyl, synthetics and laminated and coated materials

Suitable for sewing such as boat and furniture upholstery, tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, footwear and orthopedic appliances.



LSW single needle series (plain)

Features

- Semi-Automatic lubrication system.
- Large vertical axis hook (2.0 times).
- Automatic hook lubrication.
- Safety clutch prevents the hook from being damaged.
- Reverse stitching.
- Special cloth guide (AT-5676) available.
- Available in "THICK THREAD VERSION"(for heavier material). Add suffix "TA" when ordering.
- Synchronized cloth puller available(LLW series).
- 18 inch long arm version available

Specifications (LSW-)

Variety	8BL
Number of needle	Single needle
Max. sewing speed	2,800(s.p.m.)
Max. stitch length	1/4" (6.2 mm)
Clearance under presser foot	by knee 5/8" (16 mm)
	by hand 21/64" (8.5 mm)
Needle bar stroke	1-5/16" (33.2 mm)
Needle(standard)	DPx17 (#22) , 135x17 (#140)
Thread	#8 (standard)
Hook	Large vertical axis hook (2.0 times)
Amount of lift of walking foot	1/8"-15/64" standard 5/32" (3 - 6 mm) (standard 4 mm)
Thread take up lever	Slide type
Lubrication	Semi-automatic type
Bed size	18-25/32"x 7" (477 x 177 mm)
Working space	10-5/32"x 4-21/64" (258 x 110 mm)
Motor	Clutch motor
Net weight(Head only)	30Kg

NOTE (1) Speed depends on threads, materials and type of operation (2) Specifications subject to change without notice

Available model version

- LSW-8BLM Single needle, compound feed and alternating pressers, edge trimming (right)
- LSW-8BLVMF Single needle, compound feed and alternating pressers, edge trimming (center)
- LSW-8LVMF Single needle, compound feed and alternating pressers, edge trimming (center), without reverse stitch



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan
Phone : +81-47-420-3561 (Overseas dept.)
Fax : +81-47-420-3560
E-mail : export@seiko-sewing.co.jp

<http://www.seiko-sewing.co.jp/>