

Class Supply List for Get Out of Town Duffle 2.0

Instructor: Mary Stipanovich 850-545-2586

Pattern: Get Out of Town Duffle 2.0 ByAnnie.com

Also known as Get out of Town Duffle II

Fabric:

1 yard of main fabric for body of bag, pockets and carrying strap pad

1 yard of lining fabric

1-1/4 yard of coordinating fabric for bindings, handle, pulls, inner pocket, etc.

This pattern is recommended for non-directional fabrics. If you choose to use directional fabrics see "Tip" under Section I. A. Cut on page 2 of pattern.

Go to www.ByAnnie.com and view her video tutorial on using directional fabrics. https://www.byannie.com/Directional_Fabrics

Mesh fabric: -7" x 18" - optional inner pocket

Zippers:

#5 Nylon handbag zippers are needed for this project.

One 10" or longer single slide for exterior pocket

One 18" or longer double slide for body of bag

If using zipper tape by the yard you need one yard and 3 zipper pulls.

Foam Stabilizer:

1 yard of ByAnnie's Soft and Stable

Interfacing:

1/4 yard of Shapeflex fusible woven interfacing - Pellon SF-101

Or use Wovenfuse1 - Gotinterfacing.com

Strapping:

1 inch wide polyester webbing/strapping - 5-1/2 yards

One Inch Hardware:

1" triangle rings - need 2

1" swivel hooks - need 2

1" wide mouth slider - need 1

Base Stabilizer: BS-120 base stabilizer 6" x 14-3/4"

Debbie can order for you.

Circle Template

We will be rounding some corners on the bag. If you do not have circular rulers, print this template:

<https://www.byannie.com/image/catalog/product-images/templates/Circle-Templates-20200902.pdf>

Bring all essential sewing supplies, and especially include:

90/14 top stitch needle

Thread #40 or #50 polyester – match fabrics

Zipper, Walking Foot, 1/4" foot

Stiletto (I like ByAnnie's stiletto)

Temporary Spray Adhesive for fabric like Odif 505

Washout marking pen or pencil or Clover chalk pens

Wonder clips

Rotary cutter, scissors, snips

Double sided adhesive tape – ByAnnie's 1/8" for zippers and more

Use 1/4" double sided basting tape for adhering straps, tabs, etc.

https://www.amazon.com/gp/product/B01AX8DDB6/ref=ppx_yo_dt_b_search_asin_title?ie=UTF8&psc=1

Fabric glue pen – I like Sewline

12mm (1/2") bias tape maker – helpful for making zipper pulls

Fabric turning tool and bodkin

Prior to Class please quilt your fabric (main and lining) and foam stabilizer.

To quilt the pieces, sandwich the 3 pieces – lining fabric wrong side up, soft and stable, and then the main fabric right side up.

- ☐ Cut one 36 x 20" from each of the main fabric, the lining fabric and the ByAnnie Soft and Stable

This is quilted and will be the bag body.

- ☐ Cut one 36" x 18" from each of the main fabric, the lining fabric and the ByAnnie Soft and Stable

This is quilted and multiple components (front and back pockets, ends and end pockets and strap pad) will be cut after it is quilted.

Refer to the general quilting instructions on page 1 of the pattern .

- Always press fabric and foam to remove wrinkles before you sandwich the pieces together.
- A temporary fabric adhesive spray (Odif 505) can be a substitute for pins to hold the layers together.
- Use a medium length machine stitch.
- Use a walking foot to quilt lines. Make a vertical line along the length or a diagonal grid with chalk or washable pen. Mark your lines or use the guide on your walking foot. Lines are about 1" apart.
- Pattern instructs us if stitching straight lines to quilt from top to bottom across the short side. See B.Quilt on page 2 of the pattern.

You can also free motion quilt these pieces in any design you prefer.

Or ask a longarm quilter to quilt the 1 yard pieces of the main fabric and the lining fabric with the soft and stable sandwiched between.

For longarm quilting I recommend Marianne Clower, The Quilt Peddler, 2915 Kerry Forest Parkway, 850-765-9928.

Cut the 36 x 20 Quilted Fabric:

1. Using the 36 x 20 quilted fabric, cut the bag body.
17" wide and 32-1/2" high.

Cut the 36 x 18 Quilting Fabric:

Using the 36 x 18 quilted fabric, cut the following:

Two - 10-1/2 x 7"w - for bag ends

Four - 6-1/2" x 7"w - for front and back pockets and end pockets

One - 4-1/2" x 7"w - for front zipper pocket

Two - 8-1/2" x 2-1/2" for strap pad

One - 6-1/2" x 2-12" for strap pad

Cut coordinating fabric:

1. The handle, carrying strap and tabs are 2-3/4" wide.
Cut 3 strips 2-3/4 x 42 or the width of fabric.
Cut 1 strip 2-3/4 x 22
Cut 1 strip 2-3/4 x 20
2. For the pocket border and bindings that are two inches wide, cut two strips that are 2" wide x the width of fabric. You will subcut them as you make the bag.
3. Stabilizer sleeve - 14-1/2" x 20"
4. Inner Pocket - 13" x 17"

Bias binding is 2-1/4" wide and you need approx. 4 yards of continuous bias binding. Need help with bias binding or mesh, wait to cut that in class.

Use the labels provided in the pattern to help you keep track of the pieces.

Class registration policy: All classes must be paid for at the time of registration. If a class is canceled due to a lack of minimum enrollment, the class fee will be refunded. Any cancellation must be made at least 72 hours in advance to receive a refund. Teachers need time to prepare class handouts and supplies. Please register early as possible to ensure your place and to avoid disappointment.

Please have working knowledge of your machine as the educator will not have time to instruct on the use of your machine

