



Serger Ruffle Zipper Bag  
Modified directions

Cutting:

Outside bag: Back	1-8" x 10"		
Outside bag: Lower Front	1-7" x 10"	Top Front	1-2 ½" x 10"
Ruffle:	1-2 ½" x 18"		
Lining:	2-8" x 10"		
Fusible Interfacing:	2-8" x 10" for lining		
Fusible Fleece	1-7" x 10" for lower outside		1-2 ½" x 10" top front
14" or longer nylon zipper			

1. Set serger for rolled hem with 12 wt. thread in upper looper. Roll hem the lower edge of ruffle piece.
2. Set serger for 4 thread overlock with 4 serger cones. Place ruffling or shirring foot on machine. Set length to 4. Set differential to 2. Ruffle the top of the ruffle strip.
3. Return regular foot to the serger. Remember to put differential back to N and length to 2.5 or 3. Width at 7.0. Clip ruffle right side up on the right side of the lower bag front. Clip the upper bag piece face down, right sides together on the ruffle. Serger keeping all raw edges together. Open and press.
4. Place cording foot on machine. Clip zipper right sides together on top edge of upper top of bag leaving at least an inch of the zipper extending out each side of the bag top. Clip a lining piece right sides together on top of the zipper. Open the zipper. With the zipper teeth in the opening of the cording foot, serger. Open and press.
5. Clip the back bag to the zipper right sides together. Clip the lining to the zipper keeping the bag front and lining right sides together. Place zipper teeth in opening of cording foot and serger. Open and press.
6. Place the regular foot on the serger. Close the zipper half way. Lay bag out with the front right sides together and the lining pieces together. Clip all around the bag. Pinch the zipper teeth together to the front of the bag. Leave an opening in the bottom of the lining for turning. Start serging about ¾ of the lining bottom piece. Serge off. Serge Each side of the bag. On the lining bottom, remember to leave an opening for turning. Turn bag to right side out. Stitch opening on a sewing machine.