

## Wave Tucked Serger Pillow

### Directions



- Draw stitching lines on the right side of the fabric panel using the frixion marking pen. This lines should follow along the 18" length and be marked parallel every 1 ½". Start in the middle and work out. Leave about 1 ½" either side that is not marked
- Prepare the serger for a 3 thread wide stitch. Use regular thread in the left needle. Use the cream colored madeira decora thread in the upper looper and the tan color in the lower looper.
- Fold the fabric along the first line, right side of the fabric showing. Place the folded edge under the presser foot and stitch the entire length along the folded edge. Using the knife as a guide to keep the fold straight, making sure not to nip the fold with the knife.
- Continue this process of folding a line and stitching until each line is stitched.
- Press the pin tucks all in one direction.

- To make the waves, draw lines every 1" perpendicular to the stitched tucks. Make the first mark in the center of your fabric.
- Prepare your serger for a chain stitch or alternatively use your regular sewing machine using regular thread.
- Begin stitching along these lines, first in one direction, making sure the tucks fold the same direction.
- Now sew the next row, making sure the tucks fold the opposite direction.
- Continue this process until all of the rows are stitched.
- Trim your tucked fabric into a rectangle (12" x 16"), this can vary a little it does not have to be the exact same size as mine.
- Convert your serger into a basic 3 thread overlock (or use your regular sewing machine).
- Attach all four flange borders.
- Stitch a double hem in each back
- Stitch backs to front creating an envelope opening
- Press
- Stitch in ditch around the seam line to create flange.