

Lullaby

Decide which quilt design you want to make...

Option 1 - Applique Quilt

Cutting Instructions (be sure to read through the instructions before cutting):

- Fussy cut a 5" circle around the motif on your 8" square
- Cut a 29" x 28" square from Fabric A for the top.
- Subcut Fabric B strip to 3" x 29" for the middle.
- Cut the Cuddle@ Suede into a 7" circle.
- From Fabric C, cut one 13" x 29" strip for the bottom and three 1 3/4" x Width of Fabric strips for binding.

Assembly Instructions:

This quilt uses the Sew and Flip method, listed under the Tips and Tricks section of www.shannonfabrics.com. Please use these instructions to prepare the backing and batting and to piece strips in each step. Sew through the top fabrics, batting, and backing. Make sure the nap is always going towards the bottom of the quilt.

1. Spray the back of the fussy cut 5" circle with the fusible spray. Place it in the center of the Cuddle@ Suede circle. Stitch down using a stright or blanket stitch. Set aside.
2. If using batting, lay it down on a flat surface. Place the backing centered exactly on top of the backing. Lifting one side of the backing at a time, spray fusible adhesive to backing fabric and smooth backing down to hold in place. Trim the batting to the same size as the backing. If not using batting, place the backing down on a flat surface, wrong side up.
3. Place the Fabric A 29" x 28" piece along the top edge of the quilt. Use fusible spray to hold in place. Using the Sew and Flip method, piece Fabric B, then Fabric C in place.
4. Spray a small amount of fusible spray to the wrong side of the Cuddle@ Suede accent piece you assembled in step 1.

4. (continued) To match the sample quilt on the cover, place it just to the left of the center of Fabric C.
5. Bind with 1 3/4" x Width of Fabric binding strips of Fabric C. (Optional: for an under turned binding, cut 2" x Width of Fabric strips.) For help with binding, see our Tips and Tricks at www.shannonfabrics.com.

Option 2 - Strip Quilt

Cutting Instructions (be sure to read through the instructions before cutting):

- Subcut Fabric A into one 17" x 29" strip, and two 7" x 29" strips.
- Subcut Fabric B into two 3" x 29" strips.
- Subcut Fabric C into two 5" x 29" strips.

Assembly Instructions:

This quilt uses the Sew and Flip method, listed under the Tips and Tricks section of www.shannonfabrics.com. Please use these instructions to prepare the backing and batting and to piece strips in each step. Sew through the top fabrics, batting, and backing.

1. Lay the backing on a flat surface, with wrong side up. If using batting, trim to the size of the backing. Place the batting centered exactly on top of the backing. Lifting one side of the batting at a time, spray fusible adhesive to backing fabric and smooth batting down to hold in place.
2. Following the image on the front cover, place your larger Fabric A strip in the middle of your batting/backing. Lift the sides and carefully spray fusible spray to the back side of your strip. Smooth down into place.
3. Using the Sew and Flip method, piece your Fabric B strips, Fabric C strips, and remaining Fabric A strips. Make sure that the nap of the fabric is always going towards the bottom of the quilt.
4. Bind with 1 3/4" x Width of Fabric binding strips of Fabric C. (Optional: for an under turned binding, cut 2" x Width of Fabric strips.) For help with binding, see our Tips and Tricks at www.shannonfabrics.com.