

Step 1

Cutting—Sashed Squares

Read through all of the instructions before you begin. All cutting dimensions include 1/4" seams.

Cutting half-square triangles from squares: 

From EACH of the 6 LIGHT prints:

- ☐ Cut 1 selvage-to-selvage strip, 3-1/2" wide, for a total of 6 LIGHT strips.
From each strip, cut 10 squares, 3-1/2" x 3-1/2", for a total of 60 squares.
- ☐ Cut 2 strips, 3-7/8" x about 26", for a total of 12 short LIGHT strips. * see note below for alternate cutting

From EACH of the 6 DARK prints:

- ☐ Cut 2 strips, 3-7/8" x about 26", for a total of 12 short DARK strips. ** see note below for alternate cutting

From the MEDIUM print:

- ☐ Cut 15 selvage-to-selvage strips, 1-1/2" wide.
- ☐ Reserve the remaining fabric for sashing.

From the seventh DARK print:

- ☐ Cut 18 selvage-to-selvage strips, 1-1/2" wide.
- ☐ Cut 2 selvage-to-selvage strips, 3-1/2" wide.
From these strips, cut a total of 20 squares, 3-1/2" x 3-1/2".
- ☐ Reserve the remaining fabric for binding.

Jeff's Notes for Alternate Cutting

Instead of cutting 3-7/8" x 26" strips, you can cut 4" x width of fabric strips. This makes the cut easier to measure and the resulting patchwork will be trimmed afterward. All other cutting directions stay the same.

* From EACH of the 6 LIGHT Prints: cut 2 strips, 4" x WOF, for a total of 12 LIGHT strips

** From EACH of the 6 DARK Prints: cut 2 strips, 4" x WOF, for a total of 12 DARK strips

Next Step: November 5th