



TRASH ENCLOSURES SHALL BE PROVIDED FOR ALL NON-RESIDENTIAL AND MULTI-FAMILY DEVELOPMENTS IN ACCORDANCE WITH THE FOLLOWING:

1. TRASH ENCLOSURES SHALL BE A MINIMUM OF SIX FEET (6') HIGH. THEY SHALL BE CONSTRUCTED OF MASONRY, CEMENT OR CONCRETE BLOCK AND SHALL HAVE VISUALLY SCREENED GATES. THE FLOOR OF THE TRASH ENCLOSURES SHALL BE A CONCRETE PAD WHICH SHALL EXTEND FIVE FEET (5') BEYOND THE OPENING OF THE TRASH ENCLOSURE.
2. THE TOP OF THE WALL ON THE ENCLOSURE SHALL BE CAPPED OR HAVE ANY VOID SPACES FILLED WITH CONCRETE.
3. CLEAR VISIBILITY FOR ALL INTERIOR DRIVE AISLES SHALL BE MAINTAINED.
4. MINIMUM ACCESS WIDTH TO ALL SOLID WASTE CONTAINERS SHALL BE 15'.
5. TRASH ENCLOSURES SHALL BE LOCATED SO AS TO MINIMIZE DISTURBANCE TO SINGLE FAMILY RESIDENTIAL DEVELOPMENT. TRASH ENCLOSURES SHALL BE AT LEAST FORTY FEET (40') AWAY FROM ANY SINGLE FAMILY RESIDENTIAL ZONING DISTRICT.

INSTALLATION OF WEEP HOLES AT THE BOTTOM OF A TRASH ENCLOSURE WALL IS RECOMMENDED FOR DRAINAGE PURPOSES.