

# Just Dotty



The joy of fabric.

#### **CREDITS & INFO**

Just Dotty Ouilt

**SIZE**: 48½" X 64½"

TECHNICAL EDITOR: LINDA SPIRIDON

THIS PROJECT IS DESIGNED FOR MAXIMUM FLEXIBILTY FOR USE WITH ANY 12 COORDINATING FAT QUARTERS

### SUPPLIES & NOTES

ROTARY CUTTER & MAT TAPE MEASURE & RULER STRAIGHT PINS

WASH, DRY AND PRESS FABRICS BEFORE BEGINNING. 1/4" SEAM ALLOWANCE UNLESS OTHERWISE NOTED. SEWING MACHINE & COORDINATING THREAD WOF = WIDTH OF FABRIC SELVEDGE TO SELVEDGE. PRESS SEAMS AS YOU GO.

#### MATERIALS NEEDED

12 FAT OUARTERS 1 YARD BACKGROUND FABRIC ½ YARD BINDING 4 YARDS BACKING


## CUTTING DIRECTIONS


FROM EACH FAT QUARTER CUT (4) 8½" SQUARES (48 TOTAL) FROM BACKGROUND FABRIC: CUT (12) 2½" X WOF STRIPS SUBCUT INTO (192) 21/2" SQUARES


#### BLOCK ASSEMBLY —


- 1. DRAW A DIAGONAL LINE ON THE BACK SIDE OF ALL 21/2" SQUARE SEE FIG 1
- 2. PLACE A MARKED 2½" SQUARE ON THE CORNERS OF EACH 8½" SQUARE RIGHT SIDES TOGETHER AND SEW ALONG DIAGONAL LINES SEE FIG 2
- 3. TRIM EXCESS LAYERS 1/4" FROM SEAM SEE FIG 3
- 4. PRESS OPEN











### OUILT ASSEMBLY —

- 5. LAYOUT BLOCKS IN ROWS FOLLOWING THE QUILT DIAGRAM FOR PLACEMENT (OR HOWEVER YOU LIKE)
- 6. SEW BLOCKS IN ROWS PRESSING EACH ROW IN OPPOSITE DIRECTIONS
- 7. SEW 8 ROWS TO COMPLETE THE QUILT TOP
- 8. LAYER THE BACKING, BATTING AND QUILT TOP
- 9. BASTE, QUILT AND BIND

## **ASSEMBLY DIAGRAM**

