

HOEDOWN

Designed by Robert Kaufman Fabrics
www.robertkaufman.com

Featuring **down on the farm**



Finished quilt measures: 57-1/2" x 79-1/2"

Pattern Level: Confident Beginner

*"I have basic block construction down
and would like to learn a new trick!"*

ROBERTKAUFMAN
F A B R I C S

For questions about this pattern, please email Patterns@RobertKaufman.com.

Fabric and Supplies Needed

Fabric amounts based on yardage that is 42" wide.

Color	Fabric	Name/SKU	Yardage	Color	Fabric	Name/SKU	Yardage
	A	AWB-16513-268 NATURE	2/3 yard		D	ETJ-9864-9 NAVY <i>*includes binding</i>	1-1/4 yard
	B	AWB-16512-268 NATURE	2/3 yard		E	ETJ-9864-155 STONE	1-1/2 yard
	C	ETJ-9864-105 GARNET	1-1/4 yard	<p>You will also need: 5 yards for backing</p>			

Copyright 2017, Robert Kaufman
For individual use only - Not for resale

Notes Before You Begin

- Read through all of the instructions before beginning.
- All of the seam allowances are 1/4" unless otherwise noted.
- Press seam allowances open unless otherwise noted.
- Width of fabric (WOF) is equal to at least 42" wide.
- Right sides together has been abbreviated to RST.
- Half-square triangle has been abbreviated to HST.
- Remember to measure twice and cut once!

Cutting Instructions

From Fabrics A and B, fussy cut a total of:
sixteen 9-1/2" squares for the panel blocks

From Fabric C, cut:
four 9-1/2" x WOF strips. Subcut:
eighty-two 2" x 9-1/2" sashing strips

From Fabric D, cut:

four 4" x WOF strips. Subcut:
thirty-eight 4" squares for the HSTs
two 3-1/2" x WOF strips. Subcut:
nineteen 3-1/2" squares
seven 2-1/4" x WOF strips for the binding

From Fabric E, cut:

four 4" x WOF strips. Subcut:
thirty-eight 4" squares for the HSTs
seven 3-1/2" x WOF strips. Subcut:
seventy-six 3-1/2" squares
three 2" x WOF strips. Subcut:
forty-eight 2" squares for the cornerstones

Assemble the Half Square Triangles

Step 1: Pair a 4" Fabric D square with a 4" Fabric E square, RST. Mark a diagonal line on the wrong side of one square. Sew 1/4" away from both sides of the marked line. Cut on the marked line, creating two half-square triangles (HSTs). Press toward the darker fabric. Trim to 3-1/2" square. Repeat with all remaining 4" Fabric D and E squares to make a total of seventy-six D/E HSTs.



Assemble the Pieced Blocks

Step 2: Arrange the four Fabric E squares, four HSTs and one Fabric D square into three rows of three. Note the fabric placement and block orientation in the Quilt Assembly Diagram.

Step 3: Sew the units together to form rows. Press the rows toward the Fabric E squares.

Step 4: Sew the rows together to form the block. Press the row seams open. The block will measure 9-1/2" square. Repeat to make nineteen pieced blocks.



Assemble the Quilt



Step 5: Arrange the panel blocks and pieced blocks together as indicated in the Quilt Assembly Diagram. Sew each row together, using sashing strips between each block and at the beginning and end of each row. Press seams toward the sashing. Repeat to make seven block rows.

Step 6: Gather six cornerstone squares and five sashing strips. Sew each row together, using cornerstones between each sashing strip and at the beginning and end of each row. Press seams toward the sashing. Repeat to make eight sashing rows.

Step 7: Sew the sashing and block rows together, pinning and nesting the seams. Press seams open or to the sashing.

Your quilt top is complete! Baste, quilt, bind and enjoy!