



## WHY YOU NEED A FABRIC CUTTER: a better way to cut™

Turn your patterns into quilts faster and more accurately with the AccuQuilt GO!® fabric cutting systems. With over 200 piecing and appliqué shapes, a GO! Fabric Cutter is a great value and gives you the confidence to make projects you never would have attempted.

## MEET THE GO! CUTTERS:

- 90% faster than rotary cutting
- Reduces fabric waste
- Accurately cuts up to 6 layers of fabric at a time
- Minimizes hand, arm and back strain

[Why you need a fabric cutter >](#)



GO! FABRIC CUTTER

GO! BABY FABRIC CUTTER

GO! BIG ELECTRIC FABRIC CUTTER

[Choose which fabric cutter is right for you >](#)

# GO! To Your Room Wall Hanging

finished size 29" x 29"



Fabric provided by Moda Fabrics

## GO!® DIES USED

- GO! Carefree Alphabet Set (55092)
- GO! Star- 2", 3", 4" (55028)
- GO! Circle-2", 3", 5" (55012)
- GO! Critters (55030)
- GO! Square-2½" Multiples (55059) or GO! Value Die (55018)
- GO! Strip Cutter-1½" (55024)
- GO! Strip Cutter-2½" (55014 or 55017)
- GO! Strip Cutter-3½" (55032)
- GO! Strip Cutter-5½" (55026)
- GO! Strip Cutter-6½" (55086)

## FABRIC REQUIREMENTS

- Fabric 1—¾ yard
- Fabric 2—¾ yard
- Fabric 3—⅝ yard (includes binding)
- Fabric 4—⅓ yard
- Applique fabrics—Fabrics 2 through 4 and scraps or fat quarters

## FABRIC REQUIREMENTS Cont.

- Fusible web—1½ yards
- Backing—1 yard
- Batting—35" x 35"

## CUTTING DIRECTIONS

Apply fusible web to the wrong side of selected fabrics following manufacturer's instructions for appliqué shapes.

### Fabric 1:

- Cut 1—6½" x 23½" rectangle across the width of fabric (WOF) for name panel
- Cut 1—5½" x 23½" rectangle across the WOF for "Room" panel
- Cut 2—3½" x 23½" rectangles across the WOF for appliqué panels

### Fabric 2:

- Cut 1—6½" x 29½" rectangle across the WOF for bottom appliqué border
- Cut 2—3½" x 20½" rectangles across the WOF for side borders
- Cut 1—2½" x 29½" rectangle across the WOF for top border

### Fabric 3:

- Cut 3—2½" strips across the WOF for binding
- Cut 1—1½" x 23½" rectangle across the WOF
- Cut 6—2½" squares

### Fabric 4:

- Cut 5—2½" squares

### Appliqué fabrics:

- Cut shapes (all with fusible web backing) from a variety of fabrics using the quilt diagram as inspiration. Cut letters for selected name. Use a leaf or scrap for apostrophe.

## SEWING DIRECTIONS

**NOTE:** Press seams toward the darker fabric or for the least bulk or as directed.

1. Remove paper backing from appliqué shapes.
2. Lay out shapes on each appliqué panel following quilt diagram.
3. Fuse shapes in place following manufacturer's instructions.
4. Appliqué edges of shapes by hand or machine.

**SEWING DIRECTIONS Cont.**

5. Pin and sew six Fabric #3 and five Fabric #4, 2½" squares together to form pieced row.
6. Lay out appliqué panels, pieced row and Fabric #3, 1½" x 23½" rectangle following quilt diagram.
7. Pin and sew together to complete quilt center.
8. Pin and sew one Fabric #2, 3½" x 20½" border rectangle to each side of quilt center. Press seams toward border.
9. Pin and sew one Fabric #2, 2½" x 29½" border rectangle to top of quilt center. Press seams toward border.
10. Pin and sew one Fabric #2, 6½" x 29½" appliquéd border rectangle to bottom of quilt center. Press seams toward border.

**QUILTING AND FINISHING**

1. Layer batting between quilt top and backing.
2. Pin or baste layers together.
3. Model was machine quilted.
4. Add binding, mitering corners.