

# WHY YOU NEED A FABRIC CUTTER:

a better way to cut™

Turn your patterns into quilts faster and more accurately with the AccuQuilt GO!® fabric cutting systems. With over 200 piecing and appliqué shapes, a GO! Fabric Cutter is a great value and gives you the confidence to make projects you never would have attempted.

MEET THE GO! CUTTERS:

- 90% faster than rotary cutting
- Accurately cuts up to 6 layers of fabric at a time
- Reduces fabric waste
- Minimizes hand, arm and back strain



**GO! FABRIC CUTTER** 

GO! BABY FABRIC CUTTER

GO! BIG ELECTRIC FABRIC CUTTER

Choose which fabric cutter is right for you >

©2015 AccuQuilt 888.258.7913 www.accuquilt.com c1510218





# GO! Scrappy Star Log Cabin Quilt

finished size 56" x 56"

Designed by Leslie Main



Fabric provided by Hoffman Fabrics

# GO!® DIES USED

- GO! Log Cabin-12" Finished (55349)
- GO! Strip Cutter-21/4" (13/4" Finished) (55053)
- GO! Strip Cutter-6½" (6" Finished) (55086)

# **FABRIC REQUIREMENTS**

- ☐ Fabric  $1-2\frac{1}{2}$  yards total (lights) 16 pieces, 22½" x 7½" (lengthwise cuts)
- Fabric 2—2½ yards total (darks) 16 pieces,  $22\frac{1}{2}$ " x  $7\frac{1}{2}$ " (lengthwise cuts)
- Fabric 3—1¾ yards (for outer border)
- Fabric 4—¾ yard (for binding)
- Backing-65" x 65"
- Batting—65" x 65"

# **CUTTING DIRECTIONS**

#### Fabric 1:

• Cut 16—(from various light fabrics): 22½" x 7½" strips on the lengthwise grain

#### Fabric 2:

• Cut 16—(from various dark fabrics): 22½" x 7½" strips on the lengthwise grain

### Fabric 3:

• Cut 6—6½" strips across the width of fabric (WOF) by using GO! Strip Cutter-6½"

#### Fabric 4:

• Cut 6—21/4" strips across the WOF by using GO! Strip Cutter-21/4"

# **SEWING DIRECTIONS**

TIP: Using mailing label stickers, label each die. (Placing the label inside away from the cutting blades.) Starting with the smallest rectangle as number one, increasing in size till you get to #12. The label number is the finished length of the log cabin log.

PIECING TIP: Press seams toward each added piece.

PIECING TIP: The unit just added should be at the top, when feeding the next unit through the machine.

- 1. Lay out pieces from one block following block diagram on following page.
- 2. Pin and sew piece 1L to the top of 1D (center block).
- 3. With the 1L square facing up, pin and sew piece 2L to the right side of 1L/1D center unit.
- 4. Pin and sew piece 2D to the bottom side of center unit.
- 5. Pin and sew piece 3D to the left side of center unit. The unit should measure  $3\frac{1}{2}$ " x  $3\frac{1}{2}$ ".
- 6. Continue adding pieces by letter following block diagram, till you reach the desired block size. For the sample quilt, make 16,  $11\frac{1}{2}$ " x  $11\frac{1}{2}$ " unfinished blocks.
- 7. Lay out blocks according to photo.
- 8. Pin and sew into rows together to complete quilt center. Press seams toward bottom of quilt.
- 9. Add Fabric #3, 6½" strips for border. Press seams toward border.

# QUILTING AND FINISHING





2 of 2

- Layer batting between quilt top and backing.
- Pin or baste layers together. 2.
- Model was machine quilted with free-motion feathers in the light, and diagonal lines in the dark.
- 4. Add binding, mitering corners.

