

WHY YOU NEED A FABRIC CUTTER:

a better way to cut™

Turn your patterns into quilts faster and more accurately with the AccuQuilt GO!® fabric cutting systems. With over 200 piecing and appliqué shapes, a GO! Fabric Cutter is a great value and gives you the confidence to make projects you never would have attempted.

MEET THE GO! CUTTERS:

- 90% faster than rotary cutting
- Accurately cuts up to 6 layers of fabric at a time
- Reduces fabric waste
- Minimizes hand, arm and back strain



GO! FABRIC CUTTER

GO! BABY FABRIC CUTTER

GO! BIG ELECTRIC FABRIC CUTTER

Choose which fabric cutter is right for you >

©2015 AccuQuilt 888.258.7913 www.accuquilt.com c1510218





GO! Scrappy Rail Fence Quilt

finished size 51" x 51'



Fabric provided by RJR Fabrics.

GO!® DIES USED

- GO! Strip Cutter-1, 1½", 2" (½", 1", 1½" Finished) (55164)
- GO! Strip Cutter-3½" (3" Finished) (55032)
- GO! Strip Cutter-2½" (2" Finished) (55017 or 55014)

FABRIC REQUIREMENTS

- Fabric 1 (Various Oranges)—2¹/₄ yards
- Fabric 2 (Various Blues)—21/4 yards
- Fabric 3 (Various Greens)—21/4 yards
- Fabric 4—¾ yard
- Batting-60" x 60"
- Backing—3½ yards

CUTTING DIRECTIONS

Fabric 1:

• Cut a total of 18—22" x 5" length of fabric strips. Lay on multi-strip die and cut out 18 of each 1", 1½" and 2" strips

Fabric 2:

• Cut a total of 21—22" x 5" length of fabric strips. Lay on multi-strip die and cut out 21 of each 1", 11/2" and 2" strips

Fabric 3:

• Cut a total of 18—22" x 5" length of fabric strips. Lay on multi-strip die and cut out 18 of each 1", 11/2" and 2" strips


• Cut 7—2½" strips (Set aside for binding)

SEWING DIRECTIONS

Pin and sew one Fabric #1, 11/2" strip to long side of one Fabric #1, 2" strip. Press towards 2" strip.



- Pin and sew one Fabric #1, 1" strip to long side of $1\frac{1}{2}$ " strip. Press towards 1½" strip to make one Fabric #1 strip set. Strip set should measure 3½" x 22".
- Repeat previous two steps to make a total of 18 Fabric #1 strip sets.
- 4. Fan fold strip set over $3\frac{1}{2}$ " strip die to cut into $3\frac{1}{2}$ " squares. One strip set should yield six $3\frac{1}{2}$ " x $3\frac{1}{2}$ " squares. Cut a total of 96, Fabric #1 squares.



- Pin and sew one Fabric #2, 1" strip to long side of $1\frac{1}{2}$ " strip. Press towards $1\frac{1}{2}$ " strip to make one Fabric #2 strip set. Strip set should measure 3½" x 22".
- 7. Repeat previous two steps to make a total of 21, Fabric #2 strip sets.
- 8. Fan fold strip set over $3\frac{1}{2}$ " strip die to cut into $3\frac{1}{2}$ " squares. One strip set should yield six 3½" x 3½" squares. Cut a total of 100, Fabric #2 squares.
- Pin and sew one Fabric #3, $1\frac{1}{2}$ " strip to long side of one Fabric #3, 2" strip. Press towards 2" strip.







SEWING DIRECTIONS CONT.

- 10. Pin and sew one Fabric #3, 1" strip to long side of 1½" strip. Press towards $1\frac{1}{2}$ " strip to make one Fabric #3, 1" strip set. Strip set should measure $3\frac{1}{2}$ " x 22".
- 11. Repeat previous two steps to make a total of 18, Fabric #3 strip sets.
- 12. Fan fold strip set over $3\frac{1}{2}$ " strip die to cut into $3\frac{1}{2}$ " squares. One strip set should yield six 3½" x 3½" squares. Cut a total of 93, Fabric #3 squares.
- 13. Lay out blocks as shown in the diagram alternating colors and turning blocks as needed. Quilt top should be 17 blocks wide and 17 blocks long.
- 14. Pin and sew blocks into rows, pressing seams in opposite direction.
- 15. Pin and sew rows together to make the center of the quilt. Press seams in the same direction.

QUILTING AND FINISHING

- Layer quilt top with batting and backing.
- 2. Pin or baste layers together.
- 3. Model was custom machine quilted.
- 4. Add binding, mitering the corners.