



Quilt Pricing

We are pleased that we can now offer long arm Edge to Edge quilting services. We do it for you, you can choose to stay and watch, or just let us do our thing.

We charge by the square foot. Price: per square foot (multiply length x width of quilt top).

Guild Members (must show Guild Card) AND Donated/Charity Quilts (proof required) - Start at \$2.99 (plus HST)/square foot dependent on the density of the stitch pattern.

Retail Customers - Start at \$3.25 (plus HST)/square foot dependent on the density of the stitch pattern.

E2E service includes thread and bobbins. Choose from a wide variety of designs on our Bernina Q24 or ask for a us to purchase a design for an additional fee of \$10.

These designs will be quilted E2E (Edge to Edge, the chosen design will flow across your quilt regardless of borders or blocks).

If unforeseen issues arise we'll give you a call to discuss before we start.

Preparing Your Quilt

Quilt Tops

Make sure your quilt is ready to be quilted! At home, please check your top to see if there are any places where seams are coming out or if there are holes, and make any necessary repairs. Press the top and check seams for consistent pressing. All quilt tops should be pressed before quilting to ensure the tops are flat and ready to quilt. Snip all loose threads on the back side. Dark loose threads may show through the top of the quilt if not trimmed. Measure your quilt top and write the measurements down. When you come in to use the machine, one of the first questions we ask is, "How big is your top?"

Quilt Backing

At the shop we insist that backing must be a minimum of 4" and not more than 10", larger than quilt top on all sides for us to professionally quilt a project. Since it is your quilt, we'll let you decide your own minimums. However, keep in mind that it is heart-breaking to work hard completing a quilt only to find that your backing is short as you roll to the end.

When sewing two or more pieces together for the backing, do not leave selvages in the seams you have sewn. The selvages have a tighter weave, and may cause your quilt to pucker because it does not stretch like the rest of the fabric. If sewing selvedge edges together, I recommend making a 1" seam, then trimming off about ½" of the selvedge seam. Press seams open, and square up your quilt backing. Measure your quilt backing and write the measurements down, because we are also going to ask, "How big is your backing?"

Batting

You may supply your own batting, or purchase batting from All About Sewing Machines. If you supply your own batting, it should be a minimum of 4" larger than your quilt top on all sides. If you are using batting that has been packaged or is overly wrinkled, place it in a dryer with a damp towel or iron it flat before you come to quilt.

Binding your quilt service will be offered in the near future.

Quilting Request/Order

Name: _____ Date in: _____

Phone: _____ Quilting Date: _____

Quilt description: _____

Top size: width _____ length _____

Backing size: width _____ length _____

Batting:

_____ Supplied by customer

_____ Hobbs Heirloom Blend 80/20, 96" wide \$14.99 on sale + HST/metre

Type of Quilting:

Edge to Edge Pattern: _____

New Pattern Fee: _____

Thread Color: _____

Special Instructions: _____

Customer Signature: _____