Panel Works

Finished Sizes: 40" x 48"

Please read all instructions before starting. All seams are 1/4".

WOF= Width of Fabric


1. Remove the salvages from the panel. Cut 3 - 3½" strips from the top or bottom of the panel. The strips can also be cut from both ends depending on your panel. Trim panel to 22" x 32".



- 2. Cut the $3\frac{1}{2}$ " strips into $14 3\frac{1}{2}$ " squares.
- 3. Cut 12 4" Squares from Fabric A. Cut in half on the diagonal.
- 4. Stitch a Fabric A triangles to the $3\frac{1}{2}$ " squares cut from the panel as shown. Press in the direction of arrows. Repeat for the other side.



Panel




Press and trim dog ears as you go.


Careful

Don't Stretch the Bias

When Pressing.

5. Stitch the units together as shown. Press






6. Cut 7 - 3" squares from Fabric A. Cut in half on the diagonal. Stitch to the end of each section.



7. Cut 2 - 1½" x 32" Fabric B strips. Stitch to both sides of the panel. Press to the panel.

8. Cut 2 - 1½" 24" Fabric B strips. Stitch to top and bottom of the panel. Press to the panel.

- 9. Cut 4 5" x WOF strips from Fabric A. (If your pieced units are a different width, cut your strips to that width.)
- 10. Stitch a strip to the end of each of the pieced units. Measure the length of the panel and border and cut the units with four pieced squares to this measurement. Stitch to the sides, press to the border.
- 11. Measure the width and cut the two units with three pieced squares to this measurement. Stitch to the top and bottom, press to the border.
- 12. Cut 4 3" x WOF strips of Fabric B, stitch to the sides and then top and bottom, press to Fabric B.
- 13. Quilt and bind using your favorite method.



©2018 Linda Kruusi Mason Panel Works