

Closet Core Carolyn Top

- Carolyn pattern - cut
- Sewing machine - must know how to operate
- Fabric - pre-washed, ironed, and cut prior to class*
- Matching or coordinating thread
- Sewing pins or clips
- Scissors - cutting shears and snips/embroidery scissors
- $\frac{3}{4}$ - 1 yard lightweight interfacing (such as P44f)**
- Piping - premade or bias cut fabric and cording***
- Fabric marking tool- not Frixion, chalk or disappearing ink
- Buttons - refer to pattern
- Button Hole foot
- Zipper or Piping foot
- Hem gauge

Optional:

- Edge Stitch foot
- Curve Ruler (for garment fitting, not quilter's ruler)
- Sewing Label or ribbon
- Button Placement Guide

* Make sure to wash and dry your fabric prior to class. Bring your remaining fabric/scraps to class. We will make a facing for your top in class and you will need your remaining fabric.

** Interfacing is for the facing pieces. You'll want to measure your facing pieces to determine the length you will need.

*** Piping is optional. You can sew a flange and omit the cording. If you go this route, you do not need a zipper or piping foot. You can omit adding an accent altogether. We will discuss each option.

If you want to make your own piping, make sure to prewash your accent fabric prior to cutting your bias strips. You will need at least $\frac{1}{3}$ yard of fabric and $2\frac{1}{2}$ yards of $\frac{1}{8}$ " cording. Cut several strips $1\frac{5}{8}$ " wide on the bias. Sew your binding strips together into one long strip measuring approximately $2\frac{1}{2}$ yards.